

Abocast 8007-2™

Heavy-duty, Flexible Sealant and Joint Filler



Applications:

An ideal product for filling joints and cracks in exposed structures such as bridges, docks, parking garages, driveways, and flat roofs. Also works well for repairing cracks and joints between concrete and steel, and installing and sealing bulkheads, windows, other framed openings, basin drains, and pipes. Can be applied to wet surfaces. Endures any weather and resists chemicals.

Features and Benefits:

- Two part polysulfide epoxy compound provides high adhesion and medium flexibility.
- Resin and hardener can be mixed in varying ratios to increase flexibility.
- Acid, alkali and fuel resistant.
- Hardens on wet surfaces and under water.
- Ideal where concrete is to be cast onto old concrete or steel and form a permanent bond.
- Offers strength and a modest degree of flexibility sufficient to resist thermal expansion and other slight relative motions

Manufactured By:



Technical Characteristics:

- Weight/gallon: Part A - 13.0 lb / 5.0 Kg; Part B - 9.6 lb / 4.3 Kg
- Induction Period: = < 5 minutes
- Pot life: 30 minutes
- Hardening time: 1-8 hours at 75° F (24° C)
- Color: Gray
- 100% Solids
- Hardness Shore A: 92 psi
- Tensile Strength (psi): 1,031
- Elongation %: 9.2
- Meets ASTM C881/882, Type III, Grade 3, Class B, C

**The above information is based upon laboratory testing. Users are urged to test the product under their own conditions.*

Instructions:

- This is a two part product: A (resin) and B (hardener).
- Mix Parts A and B in the ratio specified on the labels.
- Apply mixture to clean, dry, surface free of contaminants, oil, grease, wax, and debris.
- Let mixture harden. When hard, application is complete.
- Refer to detailed instructions accompanying product.

Packaging:

- 2 Quart Kit
- 2 Gallon Kit
- 10 Gallon Kit

LIMITED WARRANTY

As uses and applications of this product are beyond the control of the manufacturer, all warranties, including the implied warranties of merchantability and fitness for a particular purpose, are excluded. In the event of manufacturing defects in the product, purchasers' remedies are limited to the replacement of the product or the refund of its purchase price. Liability for consequential damages is expressly excluded.

WARNING! IRRITANT.
KEEP OUT OF REACH OF CHILDREN.
Read statements on containers before using.

5501-95th Avenue
Kenosha, Wisconsin 53144 USA
1-800-445-1754
www.abatron.com

ISO 9001/2015 Registered. Made in USA.